LINK SLAB DESIGN TABLES AASHTO TYPE IV (54") GIRDERS

"B" Bar Size and Spacing in <i>Top</i> of Link Slab									
Girder	Girder Length (Brg. to Brg.) (ft)								
Spacing	≤ 75'	80'	85'	90'	95'	100'			
6'-6"									
6'-9"									
7'-0"									
7'-3"									
7'-6"									
7'-9"					#5 @ 6"				
8'-0"									
8'-3"									
8'-6"									
8'-9"									
9'-0"									
9'-3"		#4 @	4 1/2"						
9'-6"		or #5 @ 6"							
9'-9"				•					
10'-0"									
10'-3"									
10'-6"									
10'-9"									
11'-0"									
11'-3"									
11'-6"									
11'-9"									
12'-0"									

"B" Bar Size and Spacing in Bottom of Link Slab										
Girder	Girder Length (Brg. to Brg.) (ft)									
Spacing	≤ 75'	80'	85'	90'	95'	100'				
6'-6"										
6'-9"	#4 @ 4 3/4"			#5 @ 4 3/4"						
7'-0"										
7'-3"										
7'-5"	#4 @ 4 1/4"			#5 @ 4 1/4"						
7'-6"										
7'-9"	#4 @ 4 3/4"			#5 @ 4 3/4"						
8'-0"										
8'-1"	#4 @ 4 1/4"			#5 @ 4 1/4"						
8'-3"										
8'-6"	#4 @ 4 3/4"			#5 @ 4 3/4"						
8'-9"			#4 @	4 1/4"						
9'-0"										
9'-3"	#4 @ 4 3/4"		#5 @ 4 3/4"							
9'-6"										
9'-9"	#4 @			4 1/4"						
10'-0"										
10'-3"										
10'-6"										
10'-9"			#4 (මු 4"						
11'-0"										
11'-3"										
11'-6"										
11'-7"			#5 (මු 7"						
11'-9"			#5 @	7 1/2"						
12'-0"										